

# MBRP

## MBRP Muffler Installation Instructions

1360214

2019-UP

Ski-Doo 900 ACE Turbo, Race Muffler

**Note:** Local regulations may limit or prohibit modification to your snowmobile's emissions system and/or the sound levels that it generates. It is your responsibility to be aware of restrictions that may apply to your intended use of this product.

**CAUTION: THIS EXHAUST IS EXTREMELY HOT WHEN THE ENGINE HAS BEEN RUNNING. ALLOW THE EXHAUST TO FULLY COOL BEFORE PERFORMING THIS INSTALLATION OR ANY OTHER WORK TO THE VEHICLE.**

1. Remove both of the side panels and the belt guard.
2. Loosen the clamp sealing the airbox to the hood and then disconnect it. It is located just above the secondary clutch.
3. Remove the (2) screws securing the gauge pod to the hood. Lift up the gauge pod and remove the storage bin.
4. Unplug the headlight connectors and the intake air sensor. The gauge pod can now be pulled back out of the way.
5. Remove the (2) screws securing the hood assembly and then slide it forward approx. 3" to disengage the locking tabs located at the front of the hood and at the gas tank. Lift the assembly off.
6. Remove the muffler retaining bolt and the spring.
7. Remove the two (2) springs from the muffler inlet. (These springs will be reused.)
8. Remove the muffler from the sled making sure the gasket stays on the outlet of the turbo pipe.
9. Remove the 3 rubber bushings from the muffler as they will be reused.
10. Insert the rubber bushings on the MBRP Powersports muffler - only 2 of these bushings will be used. Be sure the bushing with the metal sleeve is installed in the upper bracket.
11. Install the MBRP Powersports muffler in the sled. Reinstall the muffler retaining bolt and the spring.
12. Reinstall the two exhaust springs on the inlet.
13. Reinstall the hood, gauge pod, storage bin, belt guard and side panels in the reverse order.

MBRP Ltd warranty applies for a two (2) year period from the date of purchase to defects in product material and workmanship and is to the original purchaser on record and for the original vehicle for which it was designed and installed. This warranty is limited, at MBRP Ltd.'s sole determination, to the repair or replacement of defective product only and does not include the cost of removal or re-installation, damage by accident, abuse, misuse or misapplication or any consequential damages however they may arise. Determination of warranty coverage shall be at the discretion of an authorized MBRP Ltd. quality engineer.

